



SIDER-CRETE, INC.

153 Regur Road
Hawkinsville, GA 31036 – USA

Ph: 478.892.9800

www.sider-crete.com

SIDER-ROOF PRIMER

SEAMLESS ELASTOMERIC WATERPROOFING CONCRETE ROOF COATING PRIMER

1.0 DESCRIPTION

1.1 General

Sider-Roof Primer is an acrylic primer specifically designed for use with **Sider-Roof**.

2.0 INSTALLATION

2.1 Surface preparation

Allow a minimum of 7 days for new concrete surfaces to cure before applying **Sider-Roof Primer**. Surfaces must be free of all bond-inhibiting materials, including dirt, efflorescence, from form oil and other foreign particles. Paint, loose or damaged material must be removed by water-blasting, sandblasting or mechanical wire brushing and repaired. Irregular surfaces must be resurfaced, patched or leveled to required tolerance and smoothness.

2.2 Application

Apply **Sider-Roof Primer** with a nylon/polyester brush, a ½” to 1-1/2” nap synthetic roller, or an airless sprayer. Allow a minim of 24 hours but no more than 10 days before applying **Sider-Roof**.

2.3 Limitations

Apply when ambient and surface temperatures are above 45° F (8° C) during application and drying period. Do not apply to overheated, excessively dry or frozen substrate nor during periods of high winds. Application during low temperature or high humidity will extend drying time. Allow 4-6 hours for coating to dry prior to being subjected to rain or heavy dew. **KEEP FROM FREEZING.**

3.0 MISCELLANEOUS

3.1 Packaging

1 gallon pails

5 gallon pails

3.2 Coverage

200 sq. ft. per 1 gallon per coat

1000 sq. ft. per 5 gallons per coat

3.3 Technical Application Assistance

For technical inquiries, contact Sider-Crete, Inc. at **Toll Free: 888-743-3750.**

3.4 Professional Qualifications

Installation shall be performed by contractors with a minimum of 5 years documented experience in roof coatings application or approved by Sider-Crete, Inc. All applicators should be able to provide several references from general contractors, architects or other applicable references for review by Sider-Crete, Inc.

3.5 Storage and Shelf Life

Store in a dry environment, away from direct sunlight, rain, and freezing temperatures. Shelf life is 6 months in the original sealed packaging, properly sheltered in a dry environment.

3.6 Clean Up

Clean tools and equipment with water after use prior to drying. Clean up and remove all debris and materials from the site caused by the installation according to federal, state and local regulations and dispose of waste in an approved landfill.

3.7 Commercial Names

SIDER-ROOF PRIMER

*And now, enjoy using **SIDER-ROOF PRIMER** and benefit from this revolutionary technology developed by Sider-Crete, Inc., innovative leaders in the construction industry since 1937.*

While every effort has been made to be comprehensive and accurate, the publisher cannot accept any liability for omissions or errors. Users should contact Sider-Crete for the product(s) referred to in this specification to ensure that any information used to make decisions about the product is as up-to-date and complete as possible.